

Abmat™ GEO FABRIC



ABMAT™ Geo-Fabric is constructed of needle punched Polyester short filaments. These filaments form a stable matrix exhibiting excellent strength and hydraulic characteristics. Allowing this product to be used for numerous situations where an economical solution is required for filtration and soil stabilisation in domestic landscaping applications.

Available in 50m rolls and convenient Handy Packs, smaller rolls sizes designed to accommodate most frequently purchased sizes.

| COLOUR | ROLL WIDTH | ROLL LENGTH |
|-----------|-----------------------------|-------------|
| Dark Grey | 1m | 7m |
| Dark Grey | 1m | 15m |
| Dark Grey | 1m | 50m |
| Dark Grey | 2m (Centre folded to 1m) | 7m |
| Dark Grey | 2m (Centre folded to 1m) | 15m |
| Dark Grey | 2m | 50m |

SPECIFICATIONS

| | |
|--|--------------------|
| Construction | Nonwoven Polyester |
| Thickness | 1.2mm |
| Weight | 120gsm |
| Tensile Strength | 4.5 kn/m |
| Tear Strength | 0.12 kn |
| Flow Rate | 250L/m2/S |
| All information contained on this sheet was accurate at the time of publication. This sheet is to be use as a general guide only. | |